## **GNU/Linux most wanted**

## Summary of most useful commands

©Copyright 2017-2005, Free Electrons. Free to share under the terms of the Creative Commons Attribution-ShareAlike 3.0 license (http://creativecommons.org)

Electronic version, sources, translations and updates: http://free-electrons.com/doc/legacy/command-line/

Thanks to Michel Blanc, Hermann J. Beckers and Thierry Grellier.

Latest update: Oct 17, 2022

#### Handling files and directories

Create a directory: mkdir dir

Create nested directories: mkdir -p dir1/dir2

Changing directories:

Changing directorie cd newdir

cd .. (parent directory)

cd - (previous directory)
cd (home directory)

cd ~bill (home directory of user bill)

Print the working (current) directory: pwd

Copy a file to another: cp source file dest file

Copy files to a directory: cp file1 file2 dir

Copy directories recursively: cp -r source\_dir dest\_dir rsync -a source dir/ dest dir/

Create a symbolic link: ln -s linked file link

Rename a file, link or directory: mv source file dest file

Remove files or links: rm file1 file2

Remove empty directories:

Remove non-empty directories: rm -rf dir

# Listing files

List all "regular" files (not starting with .) in the current directory:

Display a long listing: ls -l

List all the files in the current directory, including "hidden" ones (starting with .):

List by time (most recent files first):

List by size (biggest files first)

List with a reverse sort order: ls - r

Long list with most recent files last: ls -ltr

#### Displaying file contents

Concatenate and display file contents: cat file1 file2

Display the contents of several files (stopping at each page):

more file1 file2 less file1 file2 (better: extra features)

Display the first 10 lines of a file: head -10 file

Display the last 10 lines of a file: tail -10 file

#### File name pattern matching

Concatenate all "regular" files:

Concatenate all "hidden" files:

Concatenate all files ending with .log: cat \*.log

List "regular" files with bug in their name:

List all "regular" files ending with . and a single character:

## Handling file contents

Show only the lines in a file containing a given substring:

grep substring file

Case insensitive search: grep -i substring file

Showing all the lines but the ones containing a substring:

grep -v substring file

Search through all the files in a directory: grep -r substring dir

Sort lines in a given file: sort file

Sort lines, only display duplicate ones once: sort -u file (unique)

# Changing file access rights

Add write permissions to the current user: chmod u+w file

Add read permissions to users in the file group:  $\mbox{chmod } \mbox{g+r file}$ 

Add execute permissions to other users:  $\mbox{chmod o+x file}$ 

Add read + write permissions to all users: chmod a+rw file

Make executable files executable by all: chmod a+rX \*

Make the whole directory and its contents accessible by all users:
chmod -R a+rX dir (recursive)

# Comparing files and directories

Comparing 2 files: diff file1 file2

Comparing 2 files (graphical): gvimdiff file1 file2 tkdiff file1 file2 meld file1 file2 Comparing 2 directories: diff -r dir1 dir2

# Looking for files

Find all files in the current (.) directory and its subdirectories with log in their name: find . -name "\*log\*"

Find all the .pdf files in dir and subdirectories and run a command on each:
find . -name "\*.pdf" -exec xpdf {} ':'

Quick system-wide file search by pattern (caution: index based, misses new files): locate "\*pub\*"

#### Redirecting command output

Redirect command output to a file: ls \*.png > image files

Append command output to an existing file: ls \*.jpg >> image\_files

Redirect command output to the input of another command:
cat \*.log | grep error

#### Job control

Show all running processes: ps -ef

Live hit-parade of processes (press P, M, T: sort by Processor, Memory or Time usage):

Send a termination signal to a process: kill <pid> (number found in ps output)

Have the kernel kill a process: kill -9 <pid>

Kill all processes (at least all user ones): kill -9 -1

Kill a graphical application: xkill (click on the program window to kill)

# File and partition sizes

Show the total size on disk of files or directories (disk usage):
du -sh dirl dir2 file1 file2

Number of bytes, words and lines in file: wc file (word count)

Show the size, total space and free space of the current partition: df - h .

Display these info for all partitions:

# Compressing

Compress a file:
gzip file (.gz format)
bzip2 file (.bz2 format, better)
lzma file (.lzma format, best compression)
xz file (.xz format, best for code)

Uncompress a file: gunzip file.gz bunzip2 file.bz2 unlzma file.lzma unxz file.xz

## Archiving

Create a compressed archive (tape archive): tar zcvf archive.tar.gz dir tar jcvf archive.tar.bz2 dir tar Jcvf archive.tar.xz dir tar --lzma -cvf archive.tar.lzma

Test (list) a compressed archive: tar tvf archive.tar.[gz|bz2|lzma|xz]

Extract the contents of a compressed archive: tar xvf archive.tar.[gz|bz2|lzma|xz]

tar options:

c: create

t: test

x: extract

j: on the fly bzip2 (un)compression

J: on the fly xz (un)compression

z: on the fly gzip (un)compression

Handling zip archives
zip -r archive.zip <files> (create)
unzip -t archive.zip (test / list)
unzip archive.zip (extract)

#### **Printina**

Send PostScript or text files to queue: lpr -Pqueue f1.ps f2.txt (local printer)

List all the print jobs in queue: lpq -Pqueue

Cancel a print job number in queue: cancel 123 queue

Print a PDF file: pdf2ps doc.pdf lpr doc.ps

View a PostScript file: ps2pdf doc.ps xpdf doc.pdf

# User management

List users logged on the system:

Show which user I am logged as:

Show which groups user belongs to: groups user

Tell more information about user:

Switch to user hulk:

Switch to super user (root):

su - (switch user)
su (keep same directory and environment)

# Time management

Wait for 60 seconds:

Show the current date:

Count the time taken by a command: time find\_charming\_prince -cute -rich

# Command help

Basic help (works for most commands): grep --help

Access the full manual page of a command: man grep

#### Misc commands

Basic command-line calculator

#### Basic system administration

Change the owner and group of a directory and all its contents:

sudo chown -R newuser.newgroup dir

Reboot the machine in 5 minutes: sudo shutdown - r + 5

Shutdown the machine now: sudo shutdown -h now

Display all available network interfaces: ifconfig -a

Assign an IP address to a network interface: sudo ifconfig eth0 207.46.130.108

Bring down a network interface: sudo ifconfig eth0 down

Define a default gateway for packets to machines outside the local network: sudo route add default gw 192.168.0.1

Delete the default route: sudo route del default

fdisk /dev/hda1

Test networking with another machine: ping 207,46,130,108

Create or remove partitions on the first IDE hard disk:

Create (format) an ext3 filesystem: mkfs.ext3 /dev/hda1

Create (format) a FAT32 filesystem: mkfs.vfat -v -F 32 /dev/hda2

Mount a formatted partition:
mkdir /mnt/usbdisk (just do it once)
sudo mount /dev/ubal /mnt/usbdisk

Mount a filesystem image (loop device):
sudo mount -o loop fs.img /mnt/fs

Unmount a filesystem: sudo umount /mnt/usbdisk

Check the system kernel version:

